## **Snap Pool Balance**

Water Balance Tests	<b>Required Range</b>	Treatment Product	<b>Period</b>
1. pH	7.2 to 7.6 pH (7.4pH is ideal)	Hydrochloric Acid 50mL per 10,000L reduces pH by 0.1	Weekly
2. Copper lons (Cu <sup>2+</sup> )	<b>0.5 to 0.6 ppM</b> (0.3 to 0.5ppM adequate in winter with <25°C water temperature and no bather load)	Bionizer Program Settings (Turn output % Up or Dn)	Weekly
3. Total Alkalinity (TA)	80 to 100 ppM	Buffer / Soda Bi-Carbonate 200gm per 10,000L increases Alkalinity by 10ppM	Monthly
4. Phosphates	< 0.2 ppM (200ppB)	Bionizer PFP Phosphate Remover See Bionizer PFP Label	Monthly
5. Calcium Hardness	200 to 250 ppM Ideal (Up to 450 ppM OK)	Hardener / Calcium Chloride 100gm per 10,000L increases Calcium Hardness by 10ppM	Monthly
6. Total Dissolved Solids (TDS)	1000 to 1500 ppM Ideal (Up to 4000 ppM OK)	<b>1 Bag Pool Salt per 25,000L</b> Bionizer is compatible with Magnesium salt	Quarterly

Please check instructions on the label of each product and add the units required to match the volume of your pool.

Your pool will sparkle & feel healthier than ever before!



## THE 2 THINGS ONCE A WEEK RULE

## **2 TESTS EACH WEEK**

Test every week (adjust if required):

**1. pH**......**7.2-7.6 pH** Never add more than 500ml of acid in one dose to lower pH per 50,000 litres. Mix acid into bucket of water before spreading over pool, always add acid to water in bucket not the other way round.

2. Copper ..... Summer : 0.5 - 0.6 ppM Winter : 0.3 - 0.5 ppM

Correct phosphate levels are as important as correct pH levels and are easily controlled by using **Bionizer PFP<sup>™</sup>** Phosphate remover. When levels of phosphates are above 200 ppB in the pool water there is a risk of algae as phosphates are food for algae.

## **3 TESTS EVERY MONTH**

(If weather/conditions are very wet/windy then do these 3 tests weekly.)

1. Total Alkalinity	80 - 100 ppM
2. Phosphates (Algae Food)	< 0.2ppM (200 ppB)
3. Calcium Hardness	200 - 250 ppM

**Follow these rules and check your Bionizer regularly** to ensure it is operating correctly and the anodes are not worn. Do these simple steps and we promise your pool will be the source of joy it was meant to be.

Using a Bionizer to manage and control your pool or spa rewards you with sparkling and healthy water which is a pleasure to swim or spa in.

If an Eco-Oxidizer is not installed, Oxidiser needs to be used in summer or when pool is in use to burn off sunscreen and body fats. This stops the water going hazy. Example: dose 2 cups (500mL)/week, add after swimming and late in the day for 50,000 litres while filter is running. Oxidise with Hydrogen Peroxide, Potassium Monopersulfate (Oxy Shock) or Liquid Chlorine.

Tips:

1. Remember to use Pool Socks on your skimmer basket (if pool is subject to abnormally high dust or foliage dropping into the water)

2. Change sand in filter every 5 years (glass media is recommended for replacement).

3. For domestic pools, you need 5 to 6 hours circulation in summer mostly in hottest part of the day. 2 to 4 hours circulation in winter.

New Pool Start Up: Two bags of salt per 50,000L may be needed in water for new or non-salt pools for initial conductivity. The Bionizer will alert your with a flashing Red Light and/or "Check Anodes" message.